

Package: wickracopilot (via r-universe)

October 7, 2026

Type Package

Title Deterministic Market-Context Copilot Core

Version 0.2.0

Description R bindings for wickra-copilot over its C ABI hub: build a Copilot from a spec JSON, drive it with command JSON and read back a ranked list of hard facts - the same protocol as the CLI and every other binding. Only the deterministic core is exposed; the LLM adapter is never reachable over the C ABI.

License MIT + file LICENSE | Apache License 2.0

URL <https://github.com/wickra-lib/wickra-copilot>

BugReports <https://github.com/wickra-lib/wickra-copilot/issues>

Encoding UTF-8

NeedsCompilation yes

SystemRequirements the wickra-copilot C ABI shared library (WKCOPILLOT_LIB) and its header (WKCOPILLOT_INC).

Depends R (>= 4.1)

Config/roxygen2/version 8.0.0

Repository <https://wickra-lib.r-universe.dev>

Date/Publication 2026-10-06 01:49:18 UTC

RemoteUrl <https://github.com/wickra-lib/wickra-copilot>

RemoteRef v0.2.0

RemoteSha 97194036ffed23b6606593a03eb019d58725cefe

RemoteSubdir bindings/r

Contents

wkcpilot_command	2
wkcpilot_new	2
wkcpilot_version	3

Index	4
--------------	----------

wkcopilot_command	<i>Apply a command JSON and return the resulting response JSON.</i>
-------------------	---

Description

Apply a command JSON and return the resulting response JSON.

Usage

```
wkcopilot_command(copilot, cmd_json)
```

Arguments

copilot	A copilot handle from [wkcopilot_new()].
cmd_json	A command JSON string.

Value

The response as a JSON string.

wkcopilot_new	<i>Build a copilot from a spec JSON string.</i>
---------------	---

Description

Build a copilot from a spec JSON string.

Usage

```
wkcopilot_new(spec_json)
```

Arguments

spec_json	A JSON spec string.
-----------	---------------------

Value

A ‘wickra_copilot’ handle (an external pointer).

wkcopilot_version	<i>The wickra-copilot library version.</i>
-------------------	--

Description

The wickra-copilot library version.

Usage

```
wkcopilot_version()
```

Value

A version string.

Index

wkcopilot_command, [2](#)
wkcopilot_new, [2](#)
wkcopilot_version, [3](#)